


IFW

**PATENT**  
#04-0036-UNI  
Case #J3711(C)

<b>CERTIFICATE OF MAILING</b>	
I hereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to:	
"Assistant Commissioner for Patents Washington, D.C. 20231"	
on May 18, 2004	
	05/18/04
KEVIN J. STEIN	Date of
Reg. No. 47,966	Signature
Attorney for Applicant(s)	

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Applicant: Beachy et al.  
Serial No.: 10/775,510  
Filed: February 10, 2004  
For: ANTIPERSPIRANT COMPOSITIONS

Edgewater, New Jersey 07020  
May 18, 2004

**SUBMISSION OF PRIORITY DOCUMENT**


Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Pursuant to rule 55(b) of the Rules of Practice in Patent Cases, Applicant(s) is/are submitting herewith a certified copy of the United Kingdom Application No. 0303104.4 filed February 11, 2003, upon which the claim for priority under 35 U.S.C. § 119 was made in the United States.

It is respectfully requested that the priority document be made part of the file history.

Respectfully submitted,

  
Kevin J. Stein  
Reg. No. 47,966  
Attorney for Applicant(s)

KJS/mt  
(201) 840-2394



**THIS PAGE BLANK (USPTO)**



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 13 February 2004

**C PAGE BLANK (USPTO)**



**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1.	Your reference	J3711(C)/sje	
<hr/>			
2.	Patent application number (The Patent Office will fill in this part)	0303104.4	
<hr/>			
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	UNILEVER PLC UNILEVER HOUSE, BLACKFRIARS LONDON, EC4P 4BQ	
	Patents ADP number (if you know it)	50426956002 ✓	
	If the applicant is a corporate body, give the country/state of its incorporation	UNITED KINGDOM	
<hr/>			
4.	Title of the invention	ANTIPERSPIRANT COMPOSITIONS	
<hr/>			
5.	Name of your agent (if you have one)	PEARCE, Timothy	
	"Address for Service" in the United Kingdom to which all correspondence should be sent (including the postcode)	PATENT DEPARTMENT, UNILEVER PLC COLWORTH HOUSE, SHARNBROOK BEDFORD, MK44 1LQ	
	Patents ADP number (if you know it)	1628003	
<hr/>			
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)      Date of filing (day / month / year)
<hr/>			
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)
<hr/>			
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES	

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	34
Claim(s)	5
Abstract	1
Drawing(s)	-



10. If you are also filing any of the following, state how many against each item.

## Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

1

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)



Date: 11-Feb-03

Sandra Jane EDWARDS, Authorised Signatory

12. Name and daytime telephone number of person to contact in the United Kingdom

Sandra Edwards, Tel 01234 22 2068

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Antiperspirant Compositions

The present invention relates to antiperspirant compositions  
5 and in particular to anhydrous compositions containing a  
particulate antiperspirant active suspended in a carrier  
fluid.

10 Technical FieldBackground and Prior Art

Antiperspirant compositions are available to consumers in a  
variety of different applicators, and in a variety of  
15 different product forms. These can include powders,  
liquids, creams, gels or soft solids and sticks. Powders  
can be sprayed or applied by a sponge, liquids can be  
sprayed or from a wipe or a roll-on contact applicator,  
creams, gels and soft solids from a dispenser in which the  
20 composition is expelled from a reservoir onto a domed  
applicator surface through apertures in it and sticks are  
normally applied from an open-ended barrel. Consumers vary  
from country to country in their preferences. In order to  
satisfy the market place widely, it is accordingly desirable  
25 for a manufacturer of antiperspirant compositions to be able  
to provide one or more composition for each applicator.

Compositions can also be classified in accordance with the  
chemical nature of a carrier fluid. Some compositions  
30 contain a distinct phase comprising water and/or a highly  
polar, hydrophylic solvent such as propylene glycol. This

phase can dissolve the antiperspirant active and the resultant product is usually a liquid or gel, optionally in the form of an emulsion. Other compositions, however, are anhydrous and comprise an apolar, water-immiscible liquid in which a particulate antiperspirant active is suspended.

5 Such anhydrous compositions can be in the form of liquids, soft solids or sticks, depending on the extent to which the carrier liquid has been thickened or solidified.

- 10 One of the attributes of antiperspirant compositions to which a significant proportion of consumers pays considerable attention is the appearance of the product. There are three occasions at which consumers consider appearance, to a greater or lesser extent. These comprise
- 15 the appearance of the product in the dispenser, the appearance of the product when dispensed onto the body, typically the axilla, and finally the appearance of the product on any clothing which may come into contact with the composition, for example if it is brushed off the skin
- 20 surface onto a black dress, skirt or trousers. The appearance of anhydrous antiperspirant compositions is significantly affected by the comparative refractive index of the carrier fluid (mixture) and of the suspended antiperspirant active and/or any other particulate materials
- 25 that are incorporated and/or by the choice of thickener, gellant or structurant that is employed to thicken or solidify the carrier. A mismatch between two or more refractive indexes causes the product to be opaque and appear white on skin or clothing. This is not liked by many
- 30 consumers.



One class of carrier fluids which has been favoured by manufacturers of antiperspirant compositions comprises hydrocarbyl substituted siloxanes or cyclosiloxanes, such as dimethicones or cyclodimethicones. Whilst such carrier liquids have many attractive characteristics, they tend to have a comparatively low refractive index in relation to particulate aluminium or aluminium/zirconium antiperspirant actives. As a consequence, compositions containing a preponderance of such silicone fluids tend to be opaque and/or appear white when applied onto skin.

It is a desideratum of antiperspirant manufacturers to be able to formulate compositions which suffer from no greater than low visible deposits, by comparison with the extent of visible deposits from conventional wax-structured antiperspirant sticks. Formulations that promise low visible deposits are taking a significant market share. It is also desirable to be able to produce formulations which are clear, but using water-immiscible carriers having their attendant sensory properties.

Various different means have been suggested for countering the formation of visible deposits from antiperspirant compositions employing cyclomethicone carrier fluids. Substitute carrier fluids can be contemplated for a significant fraction or all of the silicone fluids, but that does not address the question of how to retain the use of silicone fluids. The refractive index of the antiperspirant active particulates can be altered, for example by control of their residual water of hydration. That is of limited value, because the change in refractive index that can be

effected is quite small in practice. Thirdly, the refractive index of silicone fluids can be increased by increasing the density of their aryl substituents relative to the commonly employed short chain alkyl, siloxanes, such as cyclomethicones. It is inherently desirable for an antiperspirant manufacturer to have the option of employing silicone fluids having a high refractive index such as at least 1.54, because this gives him considerable flexibility in creating carrier mixtures for suspending antiperspirant solids with a reasonable or very close refractive index matching. Commonly, materials with such a refractive index are obtainable with a high aryl density, but those on the market can be obtained by substituting a significant fraction of the methyl groups in a di or polymethicone substrate by phenyl groups.

Although this third route can be effective to some extent, it becomes progressively difficult and expensive to carry out the substitution reaction for an increasing proportion of aryl substituents, and in particular when greater than one aryl substituent per silicon atom is desired. Without being bound by any single theory, aryl groups are comparatively large so that substitution reactions can suffer from steric hindrance, and the presence of an existing aryl substituent can increase the barrier activation energy for a subsequent substitution. Accordingly, the production of phenyl substituted siloxanes having a high refractive index, on a bulk scale, can entail very long reaction times, and/or precise or extreme operating conditions. Such processes can be inherently expensive to operate and control, so that the resultant

product is intrinsically expensive to produce. Mass market antiperspirant compositions are price sensitive so that phenyl substituted siloxanes produced hitherto with high aryl density are not affordable for incorporation as the carrier or main carrier liquid in such compositions compared with the low refractive index cyclomethicones. That is because a carrier fluid represents a substantial fraction of the composition, commonly at least 30% of its weight and often from 40 to 70% of its weight. As far as antiperspirant manufacturers are concerned, they still have a hitherto unsatisfied want for a silicone fluid having an acceptably high aryl density that is made by a route that is more affordable.

There is described in WO 99/52965 (USP 6395704 and USP6437163) a process for making silicone fluids employing a hydrosilation reaction with a vinyl reagent. This patent family contemplates the preparation of a wide range siloxane fluids. The minimum number vinyl residues Z is 1 for 6 silicon atoms, Z being a polar or polarisable radical and the remainder of substituents on the silicon atoms being alkyl groups containing from 1 up to 8 carbons. The text is seeking to identify fluids for use with perfumes, by meeting a number of Hansen solubility parameters. Although the perfumes and siloxane fluids are contemplated for use in cosmetic compositions, including antiperspirant compositions, the patents do not consider the problem of refractive index matching, and unsurprisingly give no teaching on how to solve that problem.

A very large number of possibilities were suggested for Z including derivatives of saturated or unsaturated C<sub>2</sub>-C<sub>10</sub> multivalent aliphatic groups, such derivatives including esters or primary or secondary amides or carboxylic acids, 5 saturated or unsaturated C<sub>6</sub>-C<sub>20</sub> haloaliphatic radicals or halocycloaliphatic radicals, or aryl radicals. Amongst the list of radicals that are named are aryl radicals, the only one that is exemplified in a working example employing styrene. The siloxanes made with that reactant would not 10 enjoy a high enough refractive index. Amongst other reactants named without supportive data, one material listed without prominence or preference is the residue of  $\alpha$ -methylstyrene dimer. Without the benefit of hindsight, there is no reason for singling out merely one possible 15 derivative from the very many derivatives similarly disclosed in the patent text, still less suitably selecting the remaining substituents appropriately in conjunction with that selected derivative to solve a problem not contemplated by the patentee.

20

#### Object of the Invention


It is an object of the present invention to ameliorate or 25 overcome one or more of the problems identified above.

#### Summary of the Invention

According to the present invention there is provided an 30 antiperspirant composition comprising

- a) from 0.5 to 50% by weight of a particulate aluminium and/or aluminium/zirconium antiperspirant active;  
b) from 30 to 95% by weight of a water-immiscible carrier fluid or mixture of fluids;  
5 c) optionally up to 40% by weight of a thickener, gellant or structurant for the carrier fluid;

in which the carrier fluid comprises an aryl substituted siloxane which satisfies the general formula



in which

n represents an average number of from 0 to 2

$R^1$   $R^2$  and  $R^3$ , which may be the same as or different from each other, each represents a group  $R^4$  of formula  $-CH_2-$   
15  $C(Ph)(R^B)-R^5-Ph$

in which  $R^B$  represents H or  $-CH_3$  and  $R^5$  represents an alkylene group containing from 0 to 3 carbon atoms, optionally branched

and not more than one of  $R^1$   $R^2$  and  $R^3$  can optionally represent  $R^C$ , namely the hydrogenated residue of a  
20 substituted vinyl group other than  $R^4$  or the residue of an aliphatic alcohol, cycloaliphatic alcohol or aralkyl alcohol

and  $R^A$  represents a  $C_1$  to  $C_4$  alkyl group

25 provided that at least 60% of all carbon atoms in substituents  $R^A$   $R^4$  and  $R^C$  are present in aryl groups.

The siloxane fluids described in the summary of the invention above have a high density of phenyl or other aryl  
30 groups, by virtue of the essential inclusion of substituents of formula  $R^4$  and the limitation of the proportion of carbon

atoms that can be present in alkyl groups. As a direct consequence of such limitations, the resultant siloxane fluid has a high refractive index, typically of at least 1.54, thereby rendering them especially useful in a carrier fluid for particulate antiperspirant actives to assist refractive index matching, even for aluminium/zirconium actives, and can do so in a manner that is more affordable than using prior produced siloxanes having high phenyl density.

Detailed Description of the Invention and Preferred Embodiments

The present invention comprises compositions containing a particulate antiperspirant salt suspended in a water-immiscible carrier fluid comprising a siloxane that is substituted by the residue of hydrogenated vinyl groups  $R^1$   $R^2$  and  $R^3$  containing two phenyl substituents, which sometimes herein may be called invention siloxanes for convenience. Although the refractive index of the siloxane varies according to its actual constitution, they usually fall within the range of from 1.54 to 1.58, a range that is especially suitable for matching with antiperspirant active particulates.

The compositions employ a linear siloxane containing from 2 to 4 silicon atoms. Nominally, each siloxane unit in the invention siloxanes is substituted by the hydrogenated residue of a substituted vinyl groups, respectively  $R^1$   $R^2$  and  $R^3$ , and optionally one of them by an alternative  $R^C$ , provided

that the criteria is met that at least 60% of carbon atoms in silicon substituents are present in aryl groups.

Commonly, the proportion of carbon atoms in silicon substituents is not higher than 80%, and in many desirable  
5 embodiments is between 70 and 77%.

In the group  $R^4$ , in many desirable embodiments,  $R^B$  represents H and  $R^5$  contains 0 carbons atoms, so that the resultant group is diphenylethyl. It will be recognised that the  
10 resultant siloxanes are especially desirable because, in general, they have a comparatively high refractive index, in many instances in the region of at least 1.55. In the absence of a capper, or indeed by suitable choice of capper, if one be desired, such diphenylethyl substituted siloxanes  
15 can have a refractive index of about 1.56 to 1.575. When  $R^4$  represents diphenyl ethyl,  $n$  is often not greater than 1, and in many instances is from 0 to 0.5. Such selections represent a preferred combination of high refractive index and comparatively low viscosity for the siloxane fluid.

20 In other embodiments,  $R^5$  in group  $R^4$  represents an alkylene group containing 2 or 3 carbons, such as  $-(CH_2)-(CH_2)-$  or  $-(CH_2)-(CH(CH_3))-$ . When  $R^B$  also represents a methyl group, a suitable example comprises the hydrogenated  
25 residue from  $\alpha$ -methyl styrene dimer. Siloxanes made using  $\alpha$ -methyl styrene dimer as reagent advantageously have little detectable odour from any residual reactant, which is of practical benefit in cosmetic products. Preferably, when  $R$  is such a residue,  $n$  is preferably 0.5 to 1.5, such as in  
30 the region of  $1.0 \pm 0.2$  on average.

In the "invention" siloxanes employed herein,  $R^A$  is a short chain alkyl group, conveniently containing up to 4 carbons, though subject to the limit. The invention is described herein particularly with respect to the use of siloxanes in which such substituents  $R^A$  are each methyl groups. It is a particularly preferred that at least 75% of  $R^A$ , and especially substantially all  $R^A$  groups are methyl, because this can maximise the refractive index of the resultant siloxane.

Herein, the siloxane molecule can be capped with a limited fraction of  $R^C$ , an substituted ethyl group that is not  $R^4$ , or with the residue of an aliphatic, cycloaliphatic or aralkyl alcohol, provided that the resultant molecule still contains at least 60% aryl carbons. Capping is particularly suitable if  $R^4$  represents diphenylethyl, in which case it could also be capped using  $\alpha$ -methyl styrene dimer. Usually not more than 20% of the total occurrences of  $R^1$ ,  $R^2$  and  $R^3$  are other than  $R^4$ , ie by a capping group and often not more than 15%, such as from 10 to 15%. The employment of such a minor fraction of an alternative group  $R^C$  can minimise the extent to which the invention siloxane has a residual content of diphenylethylene or can vary the viscosity of products made using  $\alpha$  methyl styrene dimer. This can be achieved by employing a substoichiometric amount of the major reactant eg diphenyl ethylene in an initial reaction stage and employing the alternative minor reactant in a second stage. By employing only a minor fraction of the alternative substituent, the impact of such a substituent on the refractive index of the siloxane can be minimised, or at least kept within a tolerable change.



Suitable alternative capping reagents are particularly preferably liquid under use conditions and include styrene, benzyl alcohol cyclohexanol, branched alkyl fatty alcohols and allyloxyethanol. Advantageously, the selection of a  
 5 residue from a reactant that itself comprises an aryl ring can enable the phenyl density to be maintained to a greater extent than if the reactant lacks an aryl substituent. It will also be recognised that where the major reactant is diphenyl ethylene, the capping reactant can comprise  $\alpha$ -  
 10 methyl styrene dimer.

Very desirably, in the invention siloxanes,  $R^1$   $R^2$  and  $R^3$  may be diphenylethyl, but that is not essential. Such siloxanes can also offer a practical processing benefit. For the  
 15 manufacture of products in which the carrier fluid is structured, so that it is solidified, possibly flowing when subjected to hand pressure, it is conventional for the structurant (gellant) to be melted or otherwise form a single phase with the carrier liquid at an elevated  
 20 temperature and for the antiperspirant composition to solidify on cooling. If there is only a narrow window between the temperature at which all the ingredients are incorporated into the composition and its solidification temperature, it is relatively difficult on a plant scale to  
 25 avoid premature solidification, such as in the pipework from the composition production unit and the composition filling station. Advantageously, the choice of diphenylethyl substituted siloxanes fluids as described herein enables the composition to enjoy a comparatively low solidification  
 30 temperature and a wide processing temperature window

compared with commercially available phenylated siloxane fluids of similar refractive index.

In the formula for the invention siloxane employed herein,  
5 the molecule can comprise simply two terminal siloxanes of formula  $R(Me)_2Si$  linked by an oxygen atom, or can contain up to average  $n=2$  interposed units of formula  $-[SiR^2R^A-O]-$

In many instances,  $n$  is a number average of not higher than 1.5. In some embodiments, and especially where  $R$  represents  
10 a diphenylethyl residue,  $n$  is in the region of 0.


It will be recognised that the viscosity of the invention siloxanes can be controlled by varying the chemical nature and proportion of the alternative substituted ethyl group,  
15 an increased proportion tending to increase the viscosity. Likewise, an increase in the length of the siloxane molecule tends to increase viscosity. Accordingly, it is possible to obtain formulations with a carrier fluid having a high refractive index and a range of viscosities, by varying the  
20 proportions of the component invention siloxanes, for example to control the dispensing of liquid formulations.

Although it is at the discretion of the manufacturer as to what proportion of the carrier mixture is provided by  
25 invention siloxane, the benefit increases as the proportion increases or the absolute proportion of the invention siloxane in the composition increases when compared with the incorporation of previous commercial siloxanes of similar refractive index. Desirably, at least 30 or 35%, preferably  
30 at least 50% and in many embodiments more preferably at least 60% by weight of the water-immiscible carrier fluid

comprises the invention siloxanes. In many instances, the proportion of invention siloxanes in the carrier fluid mixture is not greater than 95%, desirably up to 90% and in a number of preferred embodiments up to 85% of the weight of the fluid mixture.

In various embodiments of the invention, the invention siloxanes can be employed in a sufficient proportion to act as a masking oil for suspended particulate antiperspirant actives. In such embodiments, the extent of masking increases as the proportion of the invention siloxanes increases in the carrier fluid mixture, up to the point at which the RI of the mixture matches that of the suspended particulate material that it is masking. Commonly, the proportion of a masking oil in a carrier fluid is from 10 to 30% by weight and particularly from 15% to 25%.

The invention siloxanes herein can be made by a hydrosilylation reaction in which a corresponding substrate satisfying the formula (when  $R^A$  is methyl)



in which n is as defined herein above is reacted with a substituted vinyl reactant, in the presence of a hydrosilation catalyst such as inorganic supported platinum or palladium catalysts, e.g. on divided carbon, in an amount of less than 5% by weight of the substrate in the presence of hydrogen at an elevated temperature, commonly from 40 to 200°C and at a pressure often from ambient up to an elevated pressure of 2500mPa. If in the intended product, the substituted vinyl reactant is solely diphenyl ethylene or  $\alpha$ -methylstyrene dimer, then

it is desirable to employ a slight excess over stoichiometry. If however, a minor fraction of the reactant comprises a different reactant, such as  $\alpha$ -methylstyrene dimer or other listed alternative reactant  $R^c$  when the major fraction of the substituent  $R^4$  derives from diphenyl ethylene, it is more convenient to conduct the reaction in two stages, the major reactant being employed in the first stage at the desired substoichiometric amount, and in a subsequent reaction, the intermediate product is capped by reaction with a slight excess of the minor reactant compared with the residual number of SiH moieties present. It is convenient to monitor the reaction, for example by periodic sampling and glc analysis and maintain reaction conditions until the SiH moieties have been reacted.

The balance of the carrier fluid can be provided by alternative water-immiscible liquids, including volatile and/or non-volatile silicone liquids, volatile and/or non-volatile hydrocarbon liquids, liquid fatty alcohols or benzyl alcohol, liquid esters of fatty alcohols, and liquid ether terminated polyalkylene glycols. Herein liquid indicates that the material has a melting point of not higher than 20°C. Preferably, such additional water-immiscible carrier materials herein have a boiling point of at least 75°C and particularly in the range of up to 150°C.

Volatile silicones are usually selected from cyclic polysiloxanes containing from 3 to 8 dialkylsiloxane groups, (cyclomethicones) especially dimethylsiloxane groups and particularly 4 and/or 5 dimethylsiloxane groups (tetra- and penta-cyclomethicones). Other useful volatile silicones can

comprise linear polysiloxanes, usually containing up to 8 and preferably 4 or 5 dialkylsiloxane groups, including terminal groups, commonly called dimethicones when both alkyl substituents are methyl. Low molecular weight liquid hydrocarbons that are volatile can comprise paraffin oils, often isoparaffin oils. Incorporation of such volatile materials as a fraction of the carrier fluid can assist in the matching of the refractive index of the suspended antiperspirant active and the carrier fluid. The refractive index of the volatile silicones is commonly in the region of 1.4 and of volatile hydrocarbons is around 1.42/1.43. Their presence can increase the rate of evaporation of carrier fluid from the skin after topical application.

Non-volatile silicone oils which can be employed in conjunction with the invention siloxanes can comprise linear alkylarylpolysiloxanes containing up to 4 or 5 siloxane silicon atoms, such as methylphenylsiloxanes often in which there is from 0.5 to 1.2 phenyl substituent per methyl substituent, as for example in DC556™ or DC704™ available from Dow Corning, Inc. Such materials have an intermediate or high refractive index, though for the reasons indicated hereinbefore the extent of the use with high refractive index is jeopardised by their cost. Other non-volatile silicones comprise intermediate and higher molecular weight linear dimethicones that are liquid at 20°C, such as members of the DC200™ series of silicone oils having a viscosity of at least 1 mPa.s, available from Dow Corning, Inc., and having a relatively low refractive index.

- 16 -

Non-volatile hydrocarbon oils, which often contain on average between 20 and 40 carbon atoms, include mineral oil and hydrogenated polydecene. Such materials have an intermediate refractive index in the region of 1.45 to 1.475.

Liquid fatty alcohols are normally branched chain alcohols containing from 12 to 25 carbons and several such desirable alcohols contain from 16 to 20 carbons, including isostearyl alcohol and octyl-decylalcohol. They have an intermediate refractive index in the region of 1.45 to 1.46. In conjunction with certain structurants, such as cyclodipeptide esters, their use can not only assist in refractive index matching, but can also aid the avoidance of premature gelation of a soft solid or stick composition as the composition cools prior to being filled into its dispensing container.

In some particularly desirable compositions, the carrier fluid mixture comprises from 20% to 35% by weight of a liquid fatty alcohol and/or a non-volatile hydrocarbon and/or alkyl benzoate, and particularly from 23 to 30% by weight. Such mixtures are especially well suited for employment in conjunction with a suspended activated antiperspirant active having an intermediate refractive index in the region of 1.53. Different proportions of the carrier constituents can be calculated to achieve a desired extent of RI matching, should the suspended antiperspirant active have a higher or lower refractive index.

- 17 -

In most of the formulations herein, the refractive index of the carrier fluid mixture and the antiperspirant active solid is matched at least loosely, such as with in 0.05 units or comparatively closely, such as within 0.005 units.

5 In some embodiments, the matching is  $\pm 0.001$  units.

The antiperspirant active employed herein comprises an astringent aluminium or zirconium salt. The proportion of antiperspirant active present in the composition according  
10 to the invention is often from 1-40% by weight of the composition, preferably at least 5% by weight and more preferably 15-30% by weight of a composition not intended for mixture with a propellant, or 15 to 50% in a base composition intended for mixture with a propellant that may  
15 be employed in order to make an aerosol composition.

Classes of suitable actives include aluminium salts, zirconium salts, aluminium and/or zirconium complexes, for example aluminium halides, aluminium hydroxy halides,  
20 zirconyl oxyhalides, zirconyl hydroxyhalides, and mixtures thereof. However, it is desirable to employ basic aluminium and/or zirconium salts, as such or complexed, suitable complexants including aminoacids, including particularly glycine, and especially salts in which the halide is  
25 chloride. Specific examples of preferred salts include activated aluminium chlorohydrate, aluminium chlorohydrate, aluminium pentachlorohydrate and aluminium zirconium chlorohydrate. Useful zirconium salts include zirconium hydroxy-chloride and zirconium oxychloride. Various  
30 generally used actives will be known to those skilled in the art. Preferred antiperspirant actives include ZAG

- 18 -

(Zirconium Aluminium Glycine), AAZG (Activated Aluminium Zirconium Glycine), and AACH (Activated Aluminium Chlorohydrate) activation for example as described in EP6739. In practice, the choice of antiperspirant employed will also  
5 take into local regulations, so that in many countries, aerosol formulations employ aluminium salts.

The antiperspirant active is present in particulate form suspended in the carrier fluid. The particle size of the  
10 antiperspirant salt is at the discretion of the producer of the composition, though in practice, it will normally comprise particles that are mainly in the diameter range of from 0.1 to 100 $\mu$ M, and in many instances providing a weight average particle diameter of from 10 to 60 $\mu$ M. The particle  
15 size and distribution will commonly also take into account the applicator in accordance with principles known to the skilled person.

The refractive index of the antiperspirant active normally  
20 falls within the range of 1.46 to 1.565. Actives containing solely aluminium species tending to occupy the middle and lower end of the range, particularly up to about 1.53. Thus, aluminium chlorohydrate, for example, as made, often has a refractive index of about 1.48 to about 1.50 and  
25 activated aluminium chlorohydrate at about 1.51 to about 1.53. Actives containing zirconium, as made, occupy the middle and upper end of the range, particularly from about 1.52 to 1.565 and especially from about 1.53 upwards, for example glycine complexes of aluminium/zirconium  
30 chlorohydrates. The residual water content of the antiperspirant active is a contributing factor to its



eventual refractive index, increasing water reducing the refractive index. Consequently, within a range of possibly 0.02 to 0.03 units, the refractive index of an active can be modified by controlling the drying of the active or by a post manufacture treatment in accordance with published procedures, in which the active is contacted with a limited proportion of water, or if desired by a polar liquid, such as a dihydric alcohol (eg ethylene or propylene glycol) for example in an amount of up to 5% by weight of the active.

10

It will be recognised that the inherent high refractive index of the invention silicone fluids enables them to be employed in conjunction with any aluminium or aluminium/zirconium active and still attain formulation clarity. The range is particularly great for the siloxanes substituted by predominantly diphenylethyl as R.

15

The carrier fluid or mixture of fluids can be thickened or solidified (structured) employing organic or inorganic thickeners, gellants or structurants known to a skilled man in the art for the respective class of carrier materials, and in the amounts needed to achieve the extent of thickening, gelling or structuring desired by the producer. The amount of such thickener, gellant or thickener is

20

usually selected within the range of from 0.1 to 30% by weight of the composition, depending on the nature of the final formulation which the producer wishes to make. Such formulations can comprise liquids of low viscosity, such as from 500 to 5000 mPa.s, which can be employed in roll on or pump-spray or squeeze-spray dispensers. Other thickened or gelled compositions comprise creams or soft solids, which

30

- 20 -

typically have a hardness of from 0.003 to 0.5 N/mm<sup>2</sup>, as measured by sphere indentation and frequently, from 0.005 up to 0.1 N/mm<sup>2</sup>. which compositions flow when subjected to mild pressure (1 to 5 psig) and are commonly dispensed through an apertured dome. Yet other compositions are in the form of sticks which retain their physical integrity and shape when subjected to similar low pressure, usually have a hardness of greater than 0.5 N/mm<sup>2</sup>, as measured by sphere indentation and are commonly dispensed through the open end of a barrel container.

It will be recognised that the choice of thickener or gellant may take into account any impact on the appearance of the product. Consequently, it is often desirable to employ oil-soluble organic agents for that purpose in order to retain at least low visible residues on the skin and possibly translucency on an applicator surface rather than insoluble inorganic particulate materials that would not be refractive index matched with the carrier fluid.

Three classes of thickeners or solidifying agents comprise polymers, which may be copolymers with polysiloxanes, non-polymeric agents which form fibres and waxes.

Suitable thickening polymers can be selected from polysaccharides esterified with a fatty acid of which one excellent example comprises dextrin palmitate: polyamides as discussed in US 5500209, such as the product available under the trade name Versamid<sup>TM</sup> that can be derived from hexamethylene diamine and adipic acid; alkylene/arylene block copolymers, for example styrene and ethylene,

propylene and/or butylene block copolymers eg SEBS block copolymers, many of which are available under the trade name Kraton™. The concentration of such polymers in the water-immiscible liquid is often selected in the range of from 1  
5 to 20%, depending on the extent of thickening or structuring required, and the effectiveness of the chosen polymer in the liquid/mixture.

One class of gellant which is desirable for some  
10 compositions by virtue of its long standing proven capability to produce firm solids and more recently in making soft solids, comprises waxes. However, the inclusion of waxes reduces the extent to which light can be transmitted through them, so that their use is of particular  
15 benefit in making opaque compositions in bulk which can exhibit low visible residues on application onto the skin.

Herein, the term wax is employed to encompass not only materials of natural origin that are solid with a waxy feel  
20 and water-insoluble at 30-40°C, but melt at a somewhat higher temperature, typically between 50 and 95°C, such as beeswax, candelilla or carnauba wax, but also materials having similar properties. Such other waxes include hydrocarbon waxes, eg paraffin wax, mineral wax and microcrystalline  
25 wax; synthetic waxes, such as polyethylene of 2000 to 10000 daltons; waxy derivatives or waxy components of natural waxes, such as ester components, either extracted or synthesised, solid ester derivatives of glyceryl or glycol, typically with linear saturated fatty acids, usually  
30 containing a significant fraction of C<sub>16-22</sub> acid residues, which may be synthesised or obtained by hydrogenating the

corresponding natural oil; petroleum waxes, waxy silicone polymers containing alkyl substituents of at least C10 chain length; and, importantly, waxy fatty alcohols, that normally are linear and often contain from 14 to 24 carbons, such as  
5 stearyl alcohol, cetyl alcohol and/or behenyl alcohol.

A further class of structurants for water-immiscible liquids that are employable herein, in accordance with their disclosure in patent literature relating to the preparation  
10 of antiperspirant formulations in soft solid or firm stick form include polymeric gellants. Examples of oil-soluble polyamides or amide/silicone copolymers are described in US6451295 or WO 9736573.

15 Yet other gellants include fibre-forming gellants, including hydroxystearic acid, such as 12-hydroxystearic acid, or ester or amide derivatives thereof, N-acyl amino acid amides and esters described in US-A-3969087, such as, in particular, N-Lauroyl-L-glutamic acid di-n-butylamide; amide  
20 derivatives as set forth in WO 98/27954 notably alkyl N,N'dialkyl succinamides; cyclic ester derivatives of aspartame; lanosterol, as set forth in US-A-6251377; amido derivatives of cyclohexane as set forth in US-A-6410003; a combination of a sterol and a sterol ester as set forth in  
25 WO 00/61096, eg  $\gamma$ -oryzanol and  $\beta$ -sitosterol; and fatty acid esters of cellobiose, such as in particular a product containing predominantly cellobiose octanonanoate and a minor fraction of cellobiose heptanonanoate.

Mixtures of materials within each class of gellant/structurant can be employed, as can mixtures of materials from two or each of the classes.

- 5 If the invention composition comprises an aerosol composition, it contains a propellant in addition to a base composition as described herein above, commonly in a weight ratio of from 95:5 to 40:60, and in many formulations, the weight ratio is from 90:10 to 50:50. The propellant is  
10 conveniently a low boiling point material, typically boiling below -5°C, for example an alkane such as propane, butane or isobutane, and possibly containing a fraction of pentane or isopentane, or a hydrofluorocarbon or fluorocarbon of similar carbon content. During filling of the aerosol  
15 canister, the propellant gas is liquified by virtue of the elevated pressure that is generated therein.

The invention compositions herein can comprise one or more optional constituents which have hither to been incorporated  
20 or proposed for incorporation in antiperspirant compositions. Such optional constituents may be liquid or solid, and normally comprise in total not more than 10% by weight of the composition. Such optional constituents can comprise sensory modifiers, such as finely divided  
25 polyethylene, such as in an amount of up to 5% by weight; fragrance, including, if desired deoperfumes, often in an amount of up to 4%, eg 0.3 to 2% by weight, colourants; skin cooling agents such as menthol; wash-off agents such as non-ionic surfactants.

The invention compositions can be made by the skilled man using methods known in the antiperspirant industry or described in published literature for the preparation of antiperspirant roll on, squeeze or pump spray cream or soft solid or firm stick compositions. Likewise, the invention compositions can be dispensed using the appropriate dispensers for such antiperspirant roll on, squeeze or pump spray cream or soft solid or firm stick compositions as have been employed or described in published literature.

Having described the invention in general terms, specific embodiments thereof will now be described more fully by way of example only.

In the examples, the new siloxane materials used were as shown in Table 1 below:-

Table 1

Siloxane							Refractive Index
	n	R <sup>A</sup>	R <sup>B</sup>		R <sup>C</sup>		
			%	group	%	reactant	
NS124	0	CH <sub>3</sub>	100	DPE	0		1.568.
NS144	1.3	CH <sub>3</sub>	100	DPE	0		1.574
NS053	0	CH <sub>3</sub>	85	DPE	15	AMSD	1.556
NS078	0	CH <sub>3</sub>	85	DPE	15	AMSD	1.561
NS065	0	CH <sub>3</sub>	85	DPE	15	AOE	1.555
NS068	0	CH <sub>3</sub>	85	DPE	15	BA	1.558
NS070	0	CH <sub>3</sub>	100	AMSD	0		1.542
NS050	1	CH <sub>3</sub>	100	AMSD	0		1.546

In Table 1, DPE represent diphenyl ethyl and AMSD represents as appropriate  $\alpha$ -methylstyrene dimer or its hydrogenated residue as is appropriate and AOE and BA represent respectively allyloxyethanol and benzyl alcohol.

5

The siloxanes in Table 1 above were made by the following methods:-

NS124, NS 144 and NS050 were made at a scale of about 150g by introducing reactant (DPE or AMSD) and siloxane substrate  
10 (tetramethyldisiloxane or pre-equilibrated tetramethyldisiloxane, pentamethyltrisiloxane and hexamethyltetrasiloxane with  $n=1$  or 1.3) at a mole ratio of 55:58 reactant : Si-H bonds into a clean dry flask providing a nitrogen blanket and fitted with agitator, water  
15 condensor, and thermocouple together with a platinum complex providing a Pt concentration of 25ppm. The reaction mixture was heated to slight reflux at about 100°C for 2-3 hours, and the temperature then increased to 128°C for a further 24 hours yielding a product have a small residual reactant  
20 content.

NS053, NS065, NS068 and NS078 were made by a two stage process at a scale of about 720g. In the first stage, DPE (500g, 2.77 moles) and tetramethyldisiloxane (200g, 1.49  
25 moles) were introduced into a clean dry flask providing a nitrogen blanket and fitted with agitator, water condensor, and thermocouple, warmed to 35°C and a platinum complex introduced to provide a Pt concentration of 25ppm. The mixture was slowly heated over about 60 minutes until reflux  
30 was achieved at 88°C, and the temperature slowly rose to 105°C over the next 4 hours. After a further 2-3 hours, the

- 26 -

reaction temperature was raised to and maintained at 125°C for a further 16 to 24 hours, whereupon the second stage was carried out in which a capping reagent (0.085 moles, AMDS, AEO or BA) was introduced and the reaction continued for a further 16 to 24 hours.

NS070 was made by introducing tetramethyldisiloxane (860g, 2.89 moles) and AMSD (220g, 1.38 moles) introduced into a clean dry flask providing a nitrogen blanket and fitted with agitator, water condensor, and thermocouple, together with a platinum catalyst at a PT concentration of 50ppm. The mixture was heated slowly to 85°C when refluxing commenced and during the next hours, the temperature reaching 108°C. The temperature was maintained for a further 24 hours, whereupon further catalyst (5ppm as Pt) was introduced and the reaction continued at 120°C for a further 24 hours.

Herein, the refractive index of respective materials were measured at room temperature (23°C) unless otherwise stated, employing a Becke line test (a standard procedure) for the antiperspirant active and an RFM340™ refractometer from Bellingham and Stanley Ltd for the new siloxane (NS) fluids. Each NS fluid was diluted with a diluent, either DC245 [RI=1.400] or Fluid AP [RI=1.447], in predetermined weight ratios, the refractive index of each mixture was measured and plotted against the weight proportion of the NS fluid. The refractive index of 100% NS fluid was determined by extrapolation.

Other materials employed were as follows:-



- 27 -

Table 2

		Brand or Supplier	Function
ISA	isostearyl alcohol	Prisorine 3515	carrier
FIN	C <sub>12-15</sub> alkyl benzoate	Finsolve TN Fintex Inc	carrier
CS1	alkylphenyl-siloxane	DC704 Dow Corning Inc	carrier
CS2	cyclomethicone D5	DC245 Dow Corning Inc	carrier
AACH	activated aluminum chlorohydrate RI = 1.530	A418 Summit	Anti-perspirant active
G1	dextrin palmitate	Chiba	thickener
G2	aspartame ester	in-house	gellant
G3	N-Lauroyl-L-glutamic acid di-n-butylamide	GP-1 Ajinimoto	gellant

Gellant G2 is the aspartame ester of Ex 1.2 in GB Patent Application No 0201164.4 in the name of Unilever plc. Its description on page 39 and the preparative process therefor given on page 38 of the specification that accompanied the aforementioned GB patent application is specifically incorporated herein.

Example 1

In this Example, gels were made of the siloxane fluids listed in Table 1 in the absence of an antiperspirant salt to identify whether the fluid was intrinsically suited as a carrier fluid for an antiperspirant composition.

The gels were prepared in 30ml clear glass bottles. The solvent and gelling agent were weighed directly into the bottle to give a total mixture weight of 10g. A small Teflon stirrer bar was placed in the bottle and the mixture stirred and heated until the cyclo dipeptide had dissolved. The bottle was then removed from the heat and the solution allowed to cool and gel under quiescent conditions.

The gelling temperature of the carrier/mixture was determined by first preparing a solution of the structurant in the carrier/mixture in glass tubes, having a diameter of 20mm and equipped with a glass thermometer resting on the bottom of the tube, in accordance with the description for Example 1 herein, and thereafter permitting the resultant solution in the tubes to cool naturally under quiescent conditions, ie without any cooling air being blown over the tubes and without the solution being stirred. External laboratory air temperature was about 23°C. Periodically, the thermometer was lifted by a few mm and if liquid had not flowed to fill the void under gravity, was carefully replaced on the tube bottom. The solution was considered to have formed a gel when it did not flow underneath the thermometer.

The gel hardness was determined by a skilled assessor of gels using a qualitative assessment by comparison with standard gels on the day after preparation. The clarity was determined by visual assessment by comparison with in-house standards.

5

Table 3

Solvent System				Gellant		Tg °C	Clarity	Hardness
Siloxane		Co-carrier						
type	% w/w	type	% w/w	type	% w/w			
NS124	75	ISA	25	G2	1.5	25	Clear	Medium
NS124	100			25G252	1.5	33	Clear	Medium
NS053	75	ISA	25	G2	1.5	36	Clear	Hard
NS053	75	ISA	25	G3	5	37	Clear	Medium
NS078	75	ISA	25	G2	1.5	30	Clear	Hard
NS065	75	ISA	25	G2	1.5	34	Clear	Hard
NS065	100			G2	1.5	55	Clear	Hard
NS068	75	ISA	25	G2	1.5	33	Clear	Hard
NS070	75	ISA	25	G2	1.5	60	Clear	Hard
NS070	75	ISA	25	G3	5	50	Clear	Hard
NS050	75	ISA	25	G2	1.5	53	Clear	Hard
NS050	75	ISA	25	G3	5	48	Clear	Hard
Comparative data								
CS1	75	ISA	25	G2	1.5	58	Clear	Hard
CS1	100			G2	1.5	98	Clear	Hard
CS1	75	ISA	25	G3	5	52	Clear	Medium

Tg - Quiescent gelling temperature

From Table 3, it can be seen that gels of similar clarity and hardness were obtainable of the new carrier siloxanes and that some of them also had the advantage of a significantly lower gelling temperature. Consequently, they were well suited to acting as a carrier for antiperspirant actives.

#### Example 2

In this Example, sticks were made in a conventional manner by dissolving the structurant combination in the carrier fluids shown in Table 4 at an elevated temperature, the particulate antiperspirant active was mixed in and the composition allowed to cool and stirred. The temperature ( $T_{pr}$ ) was noted at which the composition appeared to be on the point of gelling.

20

25

30

Table 4

Ex/Comp	2.1	2.2	2.3	2.4	C1
G2	1.5	1.5	1.5	1.5	1.5
G3	4.0	4.0	4.0	4.0	4.0
ISA	18.86	17.38	17.38	11.09	17.36
NS053	49.64				
NS065			52.12		
NS068		52.12			
NS070				58.41	
CS1					52.14
AACH	25.0	25.0	25.0	25.0	25.0
Fragrance	1.0				
Properties					
T <sub>pr</sub> (°C)	65	67	69	87	85
Hardness (mm)	12.1	15.0	13.3	11.1	13.1
Clarity (%T)	5.9	15.8	7.2	7.3	15.4

None of Example sticks Ex2.1 to 2.4 left a white residue  
 5 when applied to skin or to clothes.

From Table 4 it can be seen that the compositions according  
 to the present invention showed an improvement in acceptable  
 temperatures for pouring them compared with a corresponding  
 10 composition in a commercially available phenylmethylsiloxane  
 carrier. The carrier employed in Examples 2.1 to 2.3  
 respectively have similar refractive index to that in  
 Comparison C1, but manifestly have a lower pouring  
 temperature, offering greater processing freedom for a  
 15 manufacturer. Even Example 2.4 shows an advantage if like  
 for like were compared, because it was able to be poured at

substantially the same temperature as C1, even though it contained less than 2/3rds as much isostearyl alcohol, a co-carrier which in fact lowers the pour temperature for compositions containing gellants G2 and G3.

5

The hardness and rigidity of the composition in Example 2 were measured by penetrometry. The procedure utilises a lab plant PNT penetrometer equipped with a Seta wax needle (weight 2.5 grams) which has a cone angle at the point of the needle specified to be  $9^{\circ}10' \pm 15'$ . A sample of the composition with a flat upper surface is used. The needle is lowered onto the surface of the composition and then a penetration hardness measurement is conducted by allowing the needle with its holder to drop under a total weight, (i.e. the combined weight of needle and holder) of 50 grams for a period of five seconds after which the depth of penetration is noted. Desirably the test is carried out at a number of points on each sample and the results are averaged. Utilising a test of this nature, an appropriate hardness for use in an open-ended dispensing container is a penetration of less than 30 mm in this test, for example in a range from 2 to 30 mm. Preferably the penetration is in a range from 5mm to 20 mm.

25 In a specific protocol for this test measurements on a stick were performed in the stick barrel. The stick was wound up to project from the open end of the barrel, and then cut off to leave a flat, uniform surface. The needle was carefully lowered to the stick surface, and then a penetration hardness measurement was conducted. This process was carried out at six different points on the stick surface.

The hardness reading quoted is the average value of the 6 measurements.

The clarity of a composition (%T) was measured by placing a sample of standardised thickness in the light path of a spectrophotometer and measuring transmittance, as a percentage of light transmitted in the absence of the gel.

This test was carried out using a dual-beam Perkin Elmer Lambda 40 spectrophotometer. The sample of composition was poured hot into a 4.5 ml cuvette made of poly(methyl-methacrylate) (PMMA) and allowed to cool to an ambient temperature of 20-25°C. Such a cuvette gives a 1 cm thickness of composition. Measurement was carried out at 580 nm, with an identical but empty cuvette in the reference beam of the spectrophotometer, after the sample in the cuvette had been held for 24 hours. A transmittance measured at any temperature in the range from 20-25°C is usually adequately accurate, but measurement is made at 22°C if more precision is required.

### Example 3

In this Example, soft solid compositions can be made by dissolving the thickener in the mixture of carrier fluids at an elevated temperature, 110°C, cooling the resultant solution to 80-85°C, stirring in the particulate AACH and when the composition has reached about 65°C, pouring it into a soft solid barrel having at its dispensing end a plurality of slits having a minor axis diameter of 3mm. A sample is

- 34 -

also poured into a 5cm cuvette to enable its light transmission to be measured.

Table 5

Ex/Comp	3.1	3.2
G1	10	10
Fin	30	3.25
NS078	35	48.75
CS2		13.0
AACH	25	25

In the formulations summarised in Table 5, the RI of the carrier oils and the antiperspirant active were designed to differ by 0.004. As a consequence, the formulations in bulk are opaque, having a % T of <1%, but the ribbons of soft solid that are extruded through the dispensing apertures are translucent.

The products leave no significant visible white deposits when applied to skin or clothes.


The use of high RI silicone oils in accordance with the present invention enables the formulator to retain the sensory benefits arising from employing a siloxane oil as the main carrier for a similar extent of RI matching. It can also permit a significant fraction of a cyclomethicone to be employed, as in Example 3.2.



Claims:

1. An anhydrous antiperspirant composition comprising  
a) from 0.5 to 50% by weight of a particulate aluminium  
and/or aluminium/zirconium antiperspirant active;  
b) from 30 to 95% by weight of a water-immiscible  
carrier fluid or mixture of fluids;  
c) optionally up to 40% by weight of a thickener,  
gellant or structurant for the carrier fluid;

in which the carrier fluid comprises an aryl  
substituted siloxane which satisfies the general  
formula



in which

n represents an average number of from 0 to 2

$R^1$   $R^2$  and  $R^3$ , which may be the same as or different from  
each other, each represents a group  $R^4$  of formula  $-CH_2-$   
 $C(Ph)(R^B)-R^5-Ph$

in which  $R^B$  represents H or  $-CH_3$  and  $R^5$  represents an  
alkylene group containing from 0 to 3 carbon atoms,  
optionally branched

and not more than one of  $R^1$   $R^2$  and  $R^3$  can optionally  
represent  $R^C$ , namely the hydrogenated residue of a  
substituted vinyl group other than  $R^4$  or a residue of an  
aliphatic alcohol, a cycloaliphatic alcohol or an  
aralkyl alcohol

and  $R^A$  represents a  $C_1$  to  $C_4$  alkyl group  
provided that at least 60% of all carbon atoms in  
substituents  $R^A$   $R^4$  and  $R^C$  are present in aryl groups.

2. A composition according to claim 1 in which  $R^4$  represent diphenylethyl.
- 5 3. A composition according to claim 1 in which  $R^4$  represent a mixture of diphenylethyl and the hydrogenated residue of  $\alpha$ -methylstyrene dimer.
- 10 4. A composition according to claim 3 in which on at least 80% of the occurrences of  $R^1$ ,  $R^2$  and  $R^3$  represents diphenyl ethyl and up to 20% of its occurrences represents the residue of  $\alpha$  methylstyrene dimer.
- 15 5. A composition according to any preceding claim in which  $R^c$  represents a residue of benzyl alcohol or allyloxy ethanol.
- 20 6. A composition according to any preceding claim in which the diphenylethyl group is present in at least 85% of the occurrences of R.
7. A composition according to any preceding claim in which n is from 0 to 1.5.
- 25 8. A composition according to any preceding claim in which n is 0.
9. A composition according to claim 5 in which the proportion of diphenylethyl group is from 85 to 90%.
- 30 10. A composition according to claim 1 in which  $R^4$  represents the residue of  $\alpha$ -methylstyrene dimer.

11. A composition according to claim 10 in which n in the formula is  $1 \pm 0.2$ .
- 5 12. A composition according to any preceding claim in which the aryl substituted siloxane comprises at least 50% by weight of the carrier fluid or mixture of fluids.
- 10 13. A composition according to claim 12 in which the aryl substituted carrier fluid comprises from 60 to 90% by weight of the mixture of carrier fluids.
- 15 14. A composition according to any preceding claim in which the mixture of carrier fluids comprises one or more water-immiscible fluids selected from volatile polycyclomethicone or linear polymethicone oils, non-volatile polymethicone oils, liquid branched aliphatic alcohol, liquid alkyl benzoate esters and liquid polyalkylene glycol ethers.
- 20 15. A composition according to claim 14 in which the carrier mixture comprises the aryl substituted siloxane fluid and the liquid branched aliphatic alcohol in a weight ratio of from 6:1 to 2:1.
- 25 16. A composition according to any preceding claim in which the carrier fluid and suspended antiperspirant active have refractive index matching within 0.005 units.
- 30 17. A composition according to any preceding claim in which the antiperspirant active is selected from aluminium chlorohydrate or activated aluminium chlorohydrate.

18. A composition according to any of claims 1 to 17 in which the antiperspirant active is selected from aluminium/zirconium chlorohydrate and complexes of aluminium/zirconium chlorohydrate with an amino acid.

5

19. A composition according to claim 18 in which the antiperspirant active is a complex of aluminium/zirconium chlorohydrate and glycine.

10 20. A composition according to any preceding claim in which the carrier fluid is thickened or solidified with an effective amount of a structurant comprising a silicone-oil-soluble polymeric gellant or non-polymeric fibre-forming gellant.

15

21. A composition according to claim 20 in which the polymeric gellant comprises a polyalkylene, a polyalkylene/polyarylene block copolymer a polyamide or a polyamide/polysiloxane copolymer.

20

22. A composition according to claim 20 in which the non-polymeric fibre-forming gellant is selected from cellobiose esters, lanosterol, a combination of a sterol and a sterol ester, hydroxystearic acid, N-acyl amino acid amides and esters, diamido derivatives of cyclohexane, amido derivatives of aliphatic di or tri-carboxylic acids, and cyclic derivatives of aspartame.

25

23. A composition according to any of claims 20 to 22 in which the proportion of structurant is selected in the range of from 2 to 15% by weight.

30

- 39 -

24. A composition according to any of claims 20 to 23 in which the composition has a hardness of at least 0.003 N/mm<sup>2</sup> by sphere indentation.

Abstract

Antiperspirant compositions containing suspended  
5 antiperspirant actives in a water-immiscible carrier leave  
visible deposits on skin or clothing unless the actives are  
masked. The carrier mixture in compositions herein comprise  
an alkylsiloxane which is substituted by a group  $R^4$  of  
formula  $-\text{CH}_2-\text{C}(\text{Ph})(\text{R}^B)-\text{R}^5-\text{Ph}$  in which  $\text{R}^B$  represents H or  
10 methyl and  $\text{R}^5$  represents an alkylene group containing 0 to 3  
carbons, and in which the proportion of aryl carbon atoms is  
at least 60%. Preferably, the substituent comprises  
diphenylethyl. Optionally, the siloxane can be capped by  
the residue of a substituted vinyl group other than  $\text{R}^4$  or an  
15 alkyl, cycloalkyl or aralkyl alcohol.